

EXAMINED BY : <i>C. H. Chiu</i>	EMERGING DISPLAY TECHNOLOGIES CORPORATION	FILE NO . CAS-0009419
APPROVED BY: <i>Yung Chang Hu</i>		ISSUE : JUN.16, 2022
		TOTAL PAGE : 12
		VERSION : 1

CUSTOMER ACCEPTANCE SPECIFICATIONS

MODEL NO. :

E V K 1 0 1 0 0 8 A B - P O E

(RoHS)

FOR MESSRS :

CUSTOMER'S APPROVAL

DATE :

BY :

EMERGING DISPLAY
TECHNOLOGIES CORPORATION

MODEL NO.	VERSION	PAGE
EVK101008AB-POE	1	0-1

RECORDS OF REVISION

DOC . FIRST ISSUE

JUN.16, 2022

DATE

REVISED
PAGE
NO.

SUMMARY

CONFIDENTIAL
Authorized for
Emerging Display Technologies Corporation Only.
Do not distribute without authorization.

TABLE OF CONTENTS

NO.	ITEM	PAGE
1.	GENERAL SPECIFICATIONS -----	1
2.	MECHANICAL SPECIFICATIONS -----	1
3.	ABSOLUTE MAXIMUM RATINGS -----	2
4.	ELECTRICAL CHARACTERISTICS -----	3
5.	TIMING CHARACTERISTICS -----	3
6.	MCU CHARACTERISTICS -----	3
7.	OPTICAL CHARACTERISTICS -----	4, 5
8.	OUTLINE DIMENSIONS -----	6
9.	DETAIL DRAWING OF DOT MATRIX -----	7
10.	BLOCK DIAGRAM -----	8, 9
11.	INTERFACE SIGNALS -----	10, 11
12.	POWER SUPPLY -----	12
13.	CAPACITIVE TOUCH PANEL SPECIFICATION -----	12

CONFIDENTIAL
Emerging Display Technologies Corporation
Do not distribute without authorization.

1. GENERAL SPECIFICATIONS

1.1 DATA SHEETS FOR EMBEDDED SYSTEM MCU DRIVER PLEASE REFER TO :

STM32H750

1.2 DATA SHEETS FOR CAPACITIVE TOUCH PANEL CONTROLLER/DRIVER PLEASE REFER TO :

ILITEK ILI2511

1.3 DATA SHEETS FOR LCD MODULE CONTROLLER/DRIVER PLEASE REFER TO :

SITRONIX ST5651CB
SITRONIX ST5021

1.4 MATERIAL SAFETY DESCRIPTION

ASSEMBLIES SHALL COMPLY WITH EUROPEAN ROHS REQUIREMENTS, INCLUDING PROHIBITED MATERIALS/COMPONENTS CONTAINING LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, POLYBROMINATED BIPHENYLS (PBB) AND POLYBROMINATED DIPHENYL ETHERS (PBDE), BIS(2-ETHYLHEXYL) PHTHALATE (DEHP), BUTYL BENZYL PHTHALATE (BBP), DIBUTYL PHTHALATE (DBP), DIISOBUTYL PHTHALATE (DIBP).

2. MECHANICAL SPECIFICATIONS

2.1 EMBEDDED SYSTEM MECHANICAL SPECIFICATIONS

(1) DISPLAY SIZE	-----	10.1 inch
(2) NUMBER OF DOTS	-----	1024(RGB)W*600H DOTS
(3) MODULE SIZE	-----	253.72W * 156.28H *13.75D(MAX.) mm (WITHOUT RJ45)
(4) VIEWING AREA	-----	223.72W *126.28H mm
(5) ACTIVE AREA	-----	222.72W * 125.28H mm
(6) DOT SIZE	-----	0.0725W * 0.2088H mm
(7) PIXEL SIZE	-----	0.2175W * 0.2088H mm
(8) LCD TYPE	-----	IPS-TFT , TRANSMISSIVE, ANTI-GLARE
(9) COLOR	-----	262K
(10) VIEWING DIRECTION	-----	SUPER WIDE VIEW
(11) BACK LIGHT	-----	LED , COLOR : WHITE
(12) INTERFACE MODE	-----	RJ45(10/100 BASE), RS485, CAN, RS232 I ² C, SPI, GPIO, USB

2.2 CAPACITIVE TOUCH PANEL MECHANICAL SPECIFICATIONS

(1) TOUCH PANEL SIZE	-----	10.1 inch
(2) OUTER DIMENSION	-----	253.72W * 156.28H mm
(3) ACTIVE AREA	-----	225.15W * 127.68H mm
(4) INPUT TYPE	-----	MULTI TOUCH *
(5) NUMBER OF TOUCH SENSOR	-----	38*21 SENSORS

*NOTE: ACCORDING TO IMPLEMENTATION DESIGN

3. ABSOLUTE MAXIMUM RATINGS

3.1 EMBEDDED SYSTEM ELECTRICAL ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN.	MAX.	UNIT	REMARK
POWER VOLTAGE FOR POE	VDC	-0.3	+57	V	
POWER VOLTAGE FOR CN2	VP_IN	-0.3	+40	V	VSS=0
INPUT VOLTAGE	VIN	-0.3	4.0	V	

3.2 ENVIRONMENTAL ABSOLUTE MAXIMUM RATINGS

ITEM	OPERATING		STORAGE		REMARK
	MIN.	MAX.	MIN.	MAX.	
AMBIENT TEMPERATURE	-20°C	70°C	-30°C	80°C	NOTE (1), (2)
HUMIDITY	NOTE (3)		NOTE (3)		WITHOUT CONDENSATION
VIBRATION	—	2.45 m/s ² (0.25 G)	—	11.76 m/s ² (1.2 G)	10~100Hz XYZ DIRECTIONS 1HR. EACH
SHOCK	—	29.4 m/s ² (3 G)	—	490 m/s ² (50 G)	10ms XYZ DIRECTIONS 1 TIME EACH
CORROSIVE GAS	NOT ACCEPTABLE		NOT ACCEPTABLE		

NOTE (1) : THE ABSOLUTE MAXIMUM RATINGS OF THIS PRODUCT SHOULD NOT BE EXCEEDED AT ANY TIME. IF THESE RATINGS ARE EXCEEDED, THE PRODUCT'S PERFORMANCE IS NOT GUARANTEED AND THE PRODUCT MAY EXPERIENCE PERMANENT DAMAGE.

NOTE (2) : BACKGROUND COLOR CHANGES SLIGHTLY DEPENDING ON AMBIENT TEMPERATURE THIS PHENOMENON IS REVERSIBLE.

NOTE (3) : Ta ≤ 60°C : 90%RH MAX (96HRS MAX).

Ta > 60°C : ABSOLUTE HUMIDITY MUST BE LOWER THAN THE HUMIDITY OF 90%RH AT 60°C(96HRS MAX).

4. ELECTRICAL CHARACTERISTICS

4.1 EMBEDDED SYSTEM ELECTRICAL CHARACTERISTICS

Ta = 25 °C

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	REMARK
POWER SUPPLY VOLTAGE FOR POE	VDC	—	42.5	48	57	V	NOTE (3)
POWER SUPPLY CURRENT FOR POE	IDC	VDC=48V	—	205	250	mA	NOTE (3)
POWER SUPPLY VOLTAGE FOR CN1	VP_IN	—	7	12	36	V	VSS=0
POWER SUPPLY CURRENT	IVP_IN	VP_IN=7V	—	1335	1600	mA	—
	IVP_IN	VP_IN=12V	—	765	920	mA	—
	IVP_IN	VP_IN=36V	—	270	324	mA	—
LED LIFE TIME	—	—	30K	—	—	HRS	NOTE (4) NOTE (5)

NOTE (1) : VIL/VIH/VOL/VOH REFER TO STM32H750 DATA SHEET

NOTE (2) : THE POWER SUPPLY OPTION SHOULD EITHER BE CN2 OR POE

NOTE (3) : FOLLOW IEEE 802.3AT TYPE B

NOTE (4) : CONDITIONS; Ta=25°C, CONTINUOUS LIGHTING

NOTE (5) : DEFINITIONS OF LIFE TIME :

LCD LUMINANCE BECOMES HALF OF THE INITIAL VALUE.

5. TIMING CHARACTERISTICS

REFER TO STM32H750 DATA SHEET

6. MCU CHARACTERISTICS

ITEM	MEMORY SIZE		REMARK
	INTERNAL	EXTERNAL	
SD RAM	1MB	16 MB	—
FLASH	128KB	64 MB	—

NOTE : THE EXTERNAL FLASH MEMORY SIZE CAN BE UP TO 128MB

7. OPTICAL CHARACTERISTICS


7.1 OPTICAL SPECIFICATIONS

Ta = 25 ± 2 °C


ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	REMARK	
VIEWING ANGLE	θ_{y+}	CR ≥ 10	$\theta_x=0^\circ$	80	85	—	deg.	NOTE (2) NOTE (3)
	θ_{y-}			80	85	—		
	θ_{x+}		$\theta_y=0^\circ$	80	85	—		
	θ_{x-}			80	85	—		
CONTRAST RATIO (CENTER)	CR	$\theta_x=0^\circ, \theta_y=0^\circ$	800	1000	—	—	NOTE (3)	
RESPONSE TIME	T _R +T _F	$\theta_x=0^\circ, \theta_y=0^\circ$	—	25	35	msec	NOTE (4)	
COLOR CHROMATICITY (CENTER)	WHITE	$\theta_x=0^\circ, \theta_y=0^\circ$ NTSC : 50 %	W _x	0.27	0.32	0.37	—	NOTE (5)
			W _y	0.295	0.345	0.395		
	RED		R _x	0.545	0.595	0.645		
			R _y	0.325	0.375	0.425		
	GREEN		G _x	0.28	0.33	0.38		
			G _y	0.525	0.575	0.625		
	BLUE		B _x	0.11	0.16	0.21		
			B _y	0.025	0.075	0.125		
THE BRIGHTNESS OF MODULE (CENTER)	B	$\theta_x=0^\circ, \theta_y=0^\circ$	680	850	—	cd/m ²	NOTE (6)	
THE UNIFORMITY OF MODULE	—		65	70	—	%	NOTE (7)	

NOTE (1) : TEST CONDITION :

AFTER STABILIZING AND LEAVING THE PANEL ALONE AT A GIVEN TEMPERATURE FOR 30 MINUTES. MEASUREMENT SHOULD BE EXECUTED IN A STABLE, WINDLESS, AND DARK ROOM.



NOTE (2) : DEFINITION OF VIEWING ANGLE :




NOTE (3) : DEFINITION OF CONTRAST RATIO (CR) :

MEASURED AT THE CENTER POINT OF MODULE

$$\text{CONTRAST RATIO (CR)} = \frac{\text{BRIGHTNESS MEASURED WHEN LCD IS AT "WHITE STATE"}}{\text{BRIGHTNESS MEASURED WHEN LCD IS AT "BLACK STATE"}}$$

NOTE (4) : DEFINITION OF RESPONSE TIME : T_R AND T_F

THE FIGURE BELOW IS THE OUTPUT SIGNAL OF THE PHOTO DETECTOR.




NOTE (5) : DEFINITION OF COLOR CHROMATICITY

(a) 100% RGB PIXEL DATA TRANSMISSION WHEN ALL THE INPUT TERMINALS OF MODULE ARE ELECTRICALLY POWERED ON.

(b) MEASURED AT THE CENTER POINT OF MODULE

NOTE (6) : MEASURED THE BRIGHTNESS OF WHITE STATE AT CENTER POINT.

NOTE (7) : (a) DEFINITION OF BRIGHTNESS UNIFORMITY




UNIT : mm

(b) THE BRIGHTNESS UNIFORMITY CALCULATING METHOD


$$\text{UNIFORMITY} = \frac{\text{MINIMUM BRIGHTNESS}}{\text{MAXIMUM BRIGHTNESS}} * 100\%$$

8. OUTLINE DIMENSIONS



FPC COATING DRAWING

9. DETAIL DRAWING OF DOT MATRIX




UNIT : mm
SCALE : NTS
NOT SPECIFIED TOLERANCE IS ± 0.1
DOTS MATRIX TOLERANCE IS ± 0.01

CONFIDENTIAL
Authorized for Emerging Display Technologies Corporation Only
Do not distribute without authorization

10. BLOCK DIAGRAM

10.1 BLOCK DIAGRAM



10.2 IMPLEMENTATION TURN-KEY SOLUTION

BUSINESS MODEL	IMPLEMENTATION	GRAPHIC DESIGN
MODEL 1	EDT	EDT
MODEL 2	EDT	CUSTOMER / THIRD PARTY
MODEL 3	CUSTOMER / THIRD PARTY	CUSTOMER / THIRD PARTY

NOTE : THE MODEL 3 WILL REQUIRE THE SOFTWARE IMPLEMENTATION BY CUSTOMER OR A THIRD PARTY. CUSTOMER OR THIRD PARTY WILL NEED TO PROVIDE A BIN OR HEX FILE TO EDT DURING INITIAL DESIGN/DEVELOPMENT STAGE OF PROJECT, AND COULD REFERENCE TouchGFX FOR THIS DEVELOPMENT.

CONFIDENTIAL
Authorized for
Emerging Display Technologies Corporation Only.
Do not distribute without authorization.

11. INTERFACE SIGNALS

11.1 CN1 RJ45 (10/100 BASE) WITH POE INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	TX+	TRANSMIT DATA(+)
2	TX-	TRANSMIT DATA(-)
3	RX+	RECEIVE DATA DATA(+)
4	VDC+	POWER INPUT(+)
5	VDC+	POWER INPUT(+)
6	RX-	RECEIVE DATA(-)
7	VDC-	POWER INPUT(-)
8	VDC-	POWER INPUT(-)

11.2 CN2 POWER SUPPLY INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	VP IN	POWER SUPPLY
2	VP EN	POWER SUPPLY ENABLE (INTERNAL PULL HIGH)
3	VSS	GROUND

11.3 CN3 RS485 INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	VSS	GROUND
2	VSS	GROUND
3	RS485A	RS485-A
4	RS485B	RS485-B
5	VSS	GROUND
6	VSS	GROUND

11.4 CN4 CAN BUS INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	VSS	GROUND
2	VSS	GROUND
3	CANL	LOW LEVEL CAN BUS SIGNAL
4	CANH	HIGH LEVEL CAN BUS SIGNAL
5	VSS	GROUND
6	VSS	GROUND

11.5 CN5 RS232 INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	VSS	GROUND
2	RTS	REQUEST TO SEND
3	TX	TRANSMIT DATA
4	RX	RECEIVE DATA
5	CTS	CLEAR TO SEND
6	VSS	GROUND

11.6 CN6 I2C INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	3V3	3.3V OUTPUT
2	I2C_SCL	CLOCK INPUT
3	I2C_SDA	DATA INPUT AND OUTPUT
4	I2C_INT	INTERRUPT SIGNAL
5	I2C_RST	RESET SIGNAL
6	VSS	GROUND

11.7 CN7 SPI INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	3V3	3.3V OUTPUT
2	SPI_NSS	CHIP SELECT SIGNAL
3	SPI_SCK	SERIAL CLOCK
4	SPI_MISO	SERIAL DATA OUTPUT
5	SPI_MOSI	SERIAL DATA INPUT
6	VSS	GROUND

11.8 CN8 GPIO INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	GPIO1	GPIO FUNCTION PER CUSTOMER REQUEST
2	GPIO2	GPIO FUNCTION PER CUSTOMER REQUEST
3	GPIO3	GPIO FUNCTION PER CUSTOMER REQUEST
4	GPIO4	GPIO FUNCTION PER CUSTOMER REQUEST
5	GPIO5	GPIO FUNCTION PER CUSTOMER REQUEST
6	GPIO6	GPIO FUNCTION PER CUSTOMER REQUEST


11.9 CN9 USB INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	VBUS	VBUS
2	DM	USB D -
3	DP	USB D+
4	ID	ID
5	VSS	GROUND

11.10 CN10 PROGRAMMING INTERFACE

PIN NO.	SYMBOL	FUNCTION
1	3V3	3.3V OUTPUT
2	SWO	SWO
3	SWDIO	DATA
4	SWCLK	CLOCK
5	NRST	RESET
6	VSS	GROUND

12. POWER SUPPLY



13. CAPACITIVE TOUCH PANEL SPECIFICATION

13.1 HARDNESS

ITEM	DESCRIPTION
SURFACE HARDNESS	7H (min)

13.2 DURABILITY

USING STEEL BALL AND FALLING ON TOUCH PANEL SURFACE, FROM THE HEIGHT MUST PASS BELOW CONDITIONS :

ITEM	CONDITION	INSPECTION METHOD	DESCRIPTION
STEEL BALL DROP TEST	WEIGHT : 67g HEIGHT OF FALL : 30 cm	VISUAL INSPECTION	SIGN OF FRACTURE OR DAMAGE IS NOT ACCEPTABLE 1 TIMES/ 1 POINTS, 25°C(CENTER TEST)

